

## SOFT MESH FABRIC

# SP-115FR

### GENERAL DESCRIPTION:

Super soft, - Good soft texture and double penetration effect, , etc.

### FEATURES:

- Texturized Warp knit fabric that is 100% Polyester
- Compatible with Dye-sub direct, Dye-sub transfer, also workable with UV& Latex inks
- Excellent durability and tear strength

### APPLICATIONS:

Mainly used for Flag &Banner applications.

### MATERIAL DETAILS:

PROPERTIES	METRIC	TEST STANDARD	IMPERIAL
Finished Material Weight	115G/sq.m	DIN EN ISO 2286-2	3.39oz/sq m
Material	100%Polyester	DIN 60001	100%Polyester
Width	Up to 320cm	ASTM D751-2006	Up to 162"
Standard Length	50±10M / 100±10M	N/M	N/M
Weave Method	Warp-Knitted 3 bar	N/A	Warp-Knitted 2 bar
Thread Density	14w 18c	ASTM D-3887, Section 12	
Shrinkage	≤ 2% (220 C, 1 min)	ISO 9866.2	
Surface	Matte		
Flame Retardance	Germany DIN 4102 - B1 /U.S.A NFPA-701	N/A	
Yellowing temperature	210 C	SUPRKC REX-C400	

Dye Direct	Dye Transfer	Silk-Screen
√	√	√
Latex	UV	...
√	√	x

## COMPATIBLE PRINTER:

Dye Direct	Dye Transfer	UV
Roland	Mutoh	HP
Mimaki	Mimaki	
Epson	Epson	
Dgen	Dgen	
Mutoh	Mutoh	

## PRODUCTION DETAILS:

<b>PACKAGE:</b>	1. 3"plastic bags, individual packing with woven bags
	2. 3"plastic bags, individual packing, hard tubes with nail/ screw
<b>WIDTH:</b>	100-320CM
<b>LENGTH:</b>	Standard Length: 50±10M / 100±10M
	Others: each roll will has one tolerance length difference ±10%
<b>DELIVERY TIME:</b>	After received deposit 15~25 days
<b>SHIPPING CONDITIONS:</b>	FOB SHANGHAI
<b>STORAGE:</b>	Make-to-order after 3 orders will keep stable storage

**NOTE:** All mentioned data above are average of test result and should not be used for the purpose of lawsuit or warranty. This information should only be used as a guide and buyers shall independently test and determine products suitability.